

Frame ploughs with safety screw device



Classic ploughs are designed for middle and deep ploughing of flat fields on every kind of soil when soil humidity enables proper work. In case of stony fields it is recommended to use plough with shear safety device which protects the machine body against damage.

The offer contains mounted ploughs that covers 2-, 3-, 4-, 5- furrow ploughs with body width of **250 mm, 300 mm and 350 mm**. Ploughs are equipped with heavy duty, cylindrical mouldboards and plough shares. Over the mouldboard there is a special device that cuts top layer of soil and move it to the furrow bottom, what ensures better coverage of plant residues. Plough is equipped with screw device for adjustment of first furrow, working depth adjustment is carried out by steel or rubber supporting wheel. The legs of height 700 mm protect the plough from clogging while stubble field ploughing. In front of last body there is a special hole to fix the cutting disc, which is non standard equipment of the machine.

Technical specification

Symbol	-	U013	U013/1		U013/2		U013/3	
Number of sections	szt.	2	3		4		5	
Section width	m	0,30	0,30	0,35	0,30	0,35	0,30	0,35
Working width	m	0,60	0,90	1,05	1,20	1,40	1,50	1,75
Working depth	mm	do 350						
Clearance between frame and ground	mm	600 / 700						
Machine weight	kg	220	300	395	450	500	535	600

Power demand	kW/HP	32 / 44	48 / 66	54 / 75	64 / 88	72 / 100	80 / 110	90 / 125
--------------	-------	------------	------------	------------	------------	-------------	-------------	-------------

Gallery



